



PRODUCT DATA SHEET

Gilliner® 1567A

DESCRIPTION

Gilliner® 1567A is a general purpose liner constructed from woven E-glass cloth with a polyester resin system. This product has good mechanical strength for use in the cargo compartment areas, bulkhead facings and blowout panels for commercial aircraft.

APPLICATIONS


Cargo liners for cargo compartment, bulkhead facings and blowout panels for aircraft.

FEATURES

- Good strength to weight ratio
- Corrosion resistant
- Fire resistant

AVAILABILITY

	Sheet Form	Roll Form
Thickness, inch (mm)	0.013 (0.28)	0.013 (0.28)
	0.023 (0.58)	0.023 (0.58)
	0.035 (0.89)	0.035 (0.89)
	0.045 (1.14)	0.045 (1.14)
	0.059 (1.50)	0.059 (1.50)
	0.070 (1.78)	
Length	Typical 144 inch (3,658 mm)	Typical 150 feet (45,720 mm)
Width	Typical 48 inch (1,219 mm)	Typical 48 inch (1,219 mm)
	Maximum 72 inch (1,829 mm)	Maximum 60 inch (1,524 mm)
Color	Natural	



CONSTRUCTION

Resin: Polyester
Reinforcement: Woven E-glass fiber cloth
Surface: Glossy

SPECIFICATIONS

- BMS8-2, Class 1 Grade A
- FAR Part 25 Appendix F Parts I and III (burn through)

HEALTH PRECAUTIONS

This product is safe to use and apply when recommended precautions are followed. Before using this product, read and understand the Safety Data Sheet (SDS), which provides information on health, physical and environmental hazards, handling precautions and first aid recommendations. A SDS is available at <https://www.thegillcorp.com/msds.php>.

For industrial use only. Keep away from children. Additional information can be found at: www.thegillcorp.com. For sales and order information call 1-626-443-6094.

PERFORMANCE PROPERTIES, TYPICAL

