


PRODUCT DATA SHEET

Gillfab® 4037

DES	DT	

 $\mbox{Gillfab}^{\mbox{\tiny{\it B}}}\mbox{ 4037}$ is a sandwich panel made with facings of fiberglass cloth reinforced epoxy







PERFORMANCE PROPERTIES, TYPICAL

Below values are typical of 4037 panels and should NOT be used as design values.

TGC Part Number		4037 Type I	4037 Type II	4037 Type III	
Thickness, inch (mm)		0.270 (6.86)	0.390 (9.91)	0.520 (13.21)	
Nominal Facing Thickness ¹ , inch (mm)		0.010/0.010 (0.254/0.254)			
Areal Weight, PSF (kg/m²)		0.29 (1.42)	0.32 (1.56)	0.35 (1.71)	
Long Beam Bending ²	Ribbon	215 (955)	130 (595)	195 (885)	
Ultimate Load, lbf (N)	Transverse	190 (855)	115 (525)	190 (845)	
Panel Shear ³	Ribbon	345 (1540)	380 (1705)	525 (2340)	
Ultimate Load, lbf (N)	Transverse	230 (1040)	300 (1330)	370 (1655)	
Climbing Drum Peel⁴	Ribbon		50 (5.65)		
Torque, in-lbf/3 in width (N-m/76 mm width)	Transverse		60 (6.75)		
Flammability		Meets FAR 25.853 App. F Part I (a)(1)(i)			